

NOTE:
THIS DRAWING IS FOR REFERENCE ONLY AND
SHOULD NOT BE USED FOR FABRICATION.
CONSULT A ANALYZER SYSTEMS ENGINEER
FOR SPECIFIC APPLICATIONS AND REQUIREMENTS.

## BILL OF MATERIAL

ITEM QTY		DESCRIPTION	MANUFACTURER	PART NUMBER
1	1	PLATE, ALUMINUM, 36" H X 30" W X 3/16" THICK	_	_
2	2	VALVE, BALL, 3/8" TF (SS)	_	-
3	2	VALVE, BALL, 3-WAY, 1/8" TF (SS)	-	-
4	6	VALVE, BALL, 1/8" TF (SS)	-	-
5	1	VALVE, CHECK, 1/3 PSIG, 1/8" TF (SS)	-	-
6	1	VALVE, CHECK, 1/3 PSIG, 3/8" TF (SS)	-	-
7	1	VALVE, RELIEF, ADJUSTABLE , 3/8" TF (SS)	-	-
8	2	GAUGE, PRESS., (2.5",GF), 100 PSIG, 1/4"TF-CBM (SS)	-	-
9	1	GAUGE, PRESS., (2.5",GF), 60 PSIG, 1/4"TF-CBM (SS)	-	-
10	1	REGULATOR, PRESS., 0-50 PSIG, 1/4"NPT-F, (SS)	-	-
11	1	FILTER, 2. MICRON 2-1/4" ELEMENT, 1/8" NPT-F (SS)	-	-
12	1	KINETIC SEPARATOR, 12" FOR LIQUID SERVICE (SS)	SHEFFIELD	SS1200LF
13	2	FLOW METER W/VALVE, (GLASS), TBD GPH, 1/4"NPT-F( SS)	-	-
14	1	FLOW METER W/VALVE, (GLASS), 30SCCM, 1/4"NPT-F (SS)	-	-
15	1	VALVE, BALL, 1/4" TF (SS)	-	-

## FILELD CONNECTION LEGEND

(CALI) - LIQUID CALIBRATION 1

(CAL2) - LIQUID CALIBRATION 2

 $\langle$  TA $\rangle$  - SAMPLE TO ANALYZER

(FA) - SAMPLE FROM ANALYZER

(PN2) - PLANT NITROGEN

(PD) - PROCESS DRAIN

## TUBE CONNECTION LEGEND

- BULKHEAD FITTING

→ REDUCE TUBE SIZE

★ - CLOSE COUPLE (AS SHORT AS PRACTICAL)

## SAMPLE SYSTEM NOTES

1. TUBING SHALL BE TYPE 316 SEAMLESS, BRIGHT ANNEALED, STAINLESS STEEL WITH D.D. AS SHOWN AND WALL THICKNESS AS FOLLOWS:

1/8" D.D. - 0.028" WALL

1/4″ □.D. - 0.035″ WALL

3/8″ □.D. - 0.035″ WALL

1/2" D.D. - 0.049" WALL

- 2. TUBE FITTINGS SHALL BE 316 STAINLESS STEEL.
- 3. ALL MOUNTING HARDWARE (NUTS, BOLTS, WASHERS, ETC.) TO BE 316SS.
- 4. TUBING SHALL BE CUT SQUARE, REAMED TO THE INSIDE DIAMETER, AND FILED SMOOTH WITH NO BURRS OR SHARP EDGES. TUBING SHALL BE BLOWN CLEAN WITH DRY AIR TO REMOVE FILINGS AFTER CUTTING.
- 5. COMPONENTS SHALL BE INSTALLED WITH FRONT ACCESS ONLY TO ALLOW CONVENIENT REMOVAL.
- 6. NPT CONNECTIONS TO COMPONENTS SHALL BE MADE WITH TEFLON TAPE.
- 7. TUBING SHALL TERMINATE AT BULKHEAD FITTINGS.
- 8. TUBING SHALL BE SUPPORTED TO PREVENT DAMAGE (MAX. SPAN OF 3 FEET) BUT ALLOW CONVENIENT ACCESS FOR REMOVAL OF COMPONENTS.

	_							
	REV.	DESCRIPTION	BY	СНК	APP.	DATE	TITLE	
1	Α	ISSUE FOR REFERENCE	Χ	Χ	Χ	1/08	LIQUID FAST	LOOP
SHEFFIELD							SCHEMATIO	
							JOB. NO.	SCALE
SEPARATOR							0801	N.T.S.
	-							REVISION
							0801-01-501	Α